





GRANITE SURFACE PLATE (DIN 876 - GRADE 00)



Digital level



Software check flatness

Jacks can adjust

- According to DIN876, grade 00 in inspection room.
- Include inspection certificate by IMS
- Hardness > 90Hs

Model	Size (mm)	Thickness (mm)	Flatness (μm)	Weight
IG-1515	150*150	50	1.0	6kg
IG-2015	200*150	50	1.0	8kg
IG-3020	300*200	50	1.3	11kg
IG-6040	600*400	100	1.9	58kg
IG-6060	600*600	100	2.2	110kg
IG-8050	800*500	100	1.9	120kg
IG-10060	1000*600	150	3.9	260kg
IG-10075	1000*750	150	4.6	330kg
IG-100100	1000*1000	150	4.6	450kg
IG-12080	1200*800	150	4.6	455kg
IG-150100	1500*1000	150	5.9	810kg
IG-160100	1600*1000	150	5.9	850kg
IG-200100	2000*1000	200	6.9	1250kg
IG-200150	2000*1500	200	6.9	2200kg
IG-200200	2000*2000	200	7.0	2450kg
IG-300150	3000*1500	250	17.7	4500kg
IG-300200	3000*2000	250	17.7	6500kg
IG-400300	4000*3000	300	26.9	9000kg

STAND FOR IG SERI



- According to IMS's standard
- Can customized
- Manufactured in the country where IMS has an office

Model	Size (mm)	Stand High (mm)	Total High (h)
IG-6040ST	500*300	900	1000
IG-6060ST	500*500	900	1000
IG-8050ST	700*400	900	1000
IG-10060ST	850*500	750	900
IG-10075ST	850*650	750	900
IG-100100ST	850*850	750	900
IG-12080ST	1050*700	750	900
IG-150100ST	1350*850	750	900
IG-160100ST	1450*850	750	900
IG-200100ST	1800*850	600	800
IG-200150ST	1800*1350	600	800
IG-200200ST	1800*1800	600	800
IG-300150ST	2600*1350	550	800
IG-300200ST	2600*1350	550	800
IG-400300ST	3500*2600	500	800

Physical properties of granite

Hardness: >90Hs

Strength compression: >200Mpa

Volume density: 4000kg/m3

Environment requirements:

Temperature: -10 - 60 degree

Humidity: <90%