



GLOSS METER (BASIC TYPE)



FEATURE

- Accurate, stable and good experience
- Adopting the D65 light source to make sure the accurate measurements
- The meter can start measuring directly after turning on, no more extra steps, that is, users can get the measurement results quickly without waiting
- QC measurement mode for auto qualification
- Providing free PC software to generate test reports
- Long battery life, energy saving and environmental protection
- The IGM-260U Gloss Meter conforms to the following standards:
ISO2813, ISO7668, ASTM D523, ASTM D2457, DIN 67530, GB/T9754, GB/T13891, GB/T7706, GB/T8807.

Standard delivery	Q'ty
Main unit	1
Base with standard gloss plate	1
Software can export excel	1
Inspections certificate	1

Model	IGM-260U
Measuring Angle	60°
Measuring Light spot	9mm*15mm
Minimum Test Material Size	20mm*10mm
Measuring Range	0-200GU
Resolution	1GU
Repeatability	0-100GU:±1GU 100-200GU:±1%
Reproducibility	0-100GU:±1GU 100-200GU:±1%
Zero Error	1GU
Indication Error	0-100GU:±3GU 100-200GU:±3%
Power Supply	Lithium rechargeable battery 3.7V@600mAh
Display	240×128 Dot Matrix
Language	Simplified Chinese, English
Charge Port	USB(Type-C)
Data Transmission	USB
Size	140*48*75mm
Weight	About 237g
Working Temperature	10~45°C, 0~85%RH (no condensation)
Storage Temperature	-10~60°C, 0~85%RH (no condensation)